


SAFETY DATA SHEET

Klean Strip Paint Thinner for CARB



HEALTH	*	1
FLAMMABILITY		2
PHYSICAL		0
PPE		X



Printed: 06/17/2014
Revision: 11/26/2013
Supersedes Revision: 01/28/2013

1. Product and Company Identification

Product Code: 1654.2D
Product Name: Klean Strip Paint Thinner for CARB
Manufacturer Information
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Phone Number: (901)775-0100
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Web site address: www.wmbarr.com
Preparer Name: W.M. Barr EHS Department (901)775-0100
Intended Use: Paint, stain, and varnish thinning.

Synonyms

GKPT94002CA, GKPT94002PCA, QKPT94003CA, GKPT94400CB, CKPT94402CA

2. Hazards Identification

GHS Classification	Placard	Key word	GHS hazard phrase
Aspiration Toxicity, Category 1	Health hazard	Danger	May be fatal if swallowed and enters airways.

GHS Hazard Phrases

H304: May be fatal if swallowed and enters airways.

GHS Precaution Phrases

No data available.

GHS Response Phrases

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

GHS Storage and Disposal Phrases

P405: Store locked up.

P501: Dispose of contents/container to ... (in accordance with local/regional/national/international regulation).

Potential Health Effects (Acute and Chronic)

INHALATION:

Vapor harmful. Danger of serious damage to health by prolonged exposure through inhalation.

SKIN CONTACT:

Prolonged skin contact may cause skin irritation and/or dermatitis.

EYE CONTACT:

Liquid contact may cause irritation.

INGESTION:

Harmful or fatal if swallowed. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

CHRONIC EFFECTS:

SAFETY DATA SHEET

Klean Strip Paint Thinner for CARB

Page: 2
Printed: 06/17/2014
Revision: 11/26/2013
Supersedes Revision: 01/28/2013

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage.

TARGET ORGANS: skin, central nervous system

PRIMARY ROUTES OF ENTRY: inhalation, skin contact

Medical Conditions Generally Aggravated By Exposure

None known.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Hydrotreated light distillate (petroleum)	64742-47-8	<100.0 %

4. First Aid Measures

Emergency and First Aid Procedures

Skin:

Wash the skin thoroughly with water and soap, if available, while removing contaminated clothing. Seek medical attention if irritation develops or persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms Of Exposure

See Potential Health Effects.

5. Fire Fighting Measures

Flammability Classification:	NFPA Class IIIA
Flash Pt:	190.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: No data. UEL: No data.
Autoignition Pt:	No data available.

Fire Fighting Instructions

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Material float on water. Do not use straight water streams, as this may spread the fire.

Flammable Properties and Hazards

Material will float on water.

SAFETY DATA SHEET

Klean Strip Paint Thinner for CARB

Page: 3
Printed: 06/17/2014
Revision: 11/26/2013
Supersedes Revision: 01/28/2013

Hazardous Combustion Products

Carbon monoxide, carbon dioxide

Suitable Extinguishing Media

Use carbon dioxide, dry powder, foam, or water spray / fog.

Unsuitable Extinguishing Media

Do not use straight water streams, as this may spread the fire.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Isolate the immediate area. Prevent unauthorized entry. Eliminate all sources of ignition in area and downwind of the spill area. Stay upwind, out of low areas, and ventilate closed spaces before entering. All equipment used when handling this product must be grounded or non-sparking. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers. For large spills, dike ahead of the spill for possible collection and reuse or disposal.

7. Handling and Storage

Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Ensure all equipment is electrically grounded before beginning transfer operations.

Avoid prolonged skin contact.

Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TLV	Other Limits
1. Hydrotreated light distillate (petroleum)	64742-47-8	No data.	200 mg/m ³	No data.

Respiratory Equipment (Specify Type)

For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

Eye Protection

Chemical splash goggles should be worn to prevent eye contact.

Protective Gloves

Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

SAFETY DATA SHEET

Klean Strip Paint Thinner for CARB

Page: 4
Printed: 06/17/2014
Revision: 11/26/2013
Supersedes Revision: 01/28/2013

Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

Engineering Controls (Ventilation etc.)

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

Work/Hygienic/Maintenance Practices

Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

9. Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid
Melting Point:	No data.
Boiling Point:	No data.
Autoignition Pt:	No data.
Flash Pt:	190.00 F Method Used: Setaf flash Closed Cup (Rapid Setaf flash)
Specific Gravity (Water = 1):	0.7693 - 0.8093
Density:	6.567 LB/GL
Vapor Pressure (vs. Air or mm Hg):	0.17 MM HG at 68.0 F
Vapor Density (vs. Air = 1):	> 1
Evaporation Rate:	< 1
Solubility in Water:	Not Soluble
Percent Volatile:	100.0 % by weight.
VOC / Volume:	2.8800 G/L
Viscosity:	water thin

Appearance and Odor

Aromatic hydrocarbon-like odor. Free and clear, water-white liquid.

Additional Physical Information

Product category, Paint Thinner, LVP solvent and is not a VOC as defined by the California Air Resources Board (CARB).

SAFETY DATA SHEET
Klean Strip Paint Thinner for CARB

Page: 5
Printed: 06/17/2014
Revision: 11/26/2013
Supersedes Revision: 01/28/2013

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability

No data available.

Incompatibility - Materials To Avoid

Incompatible with oxidizing agents.

Hazardous Decomposition Or Byproducts

Thermal decomposition may produce carbon monoxide and carbon dioxide.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions

No data available.

11. Toxicological Information

Toxicological Information

CAS# 64742-47-8:

Acute toxicity, LC50, Inhalation, Rat, 1400. ppm.

Result:

Behavioral: Hallucinations, distorted perceptions.

Behavioral: Change in motor activity (specific assay).

Behavioral: Changes in psychophysiological tests.

Standard Draize Test, Eyes, Human, 100.0 ppm, Mild.

Result:

Brain and Coverings: Recordings from specific areas of CNS.

Behavioral: Antipsychotic.

Blood: Changes in bone marrow not included above.

Chronic Toxicological Effects

No data available.

Carcinogenicity/Other Information

ACGIH A4 - Not Classifiable as a Human Carcinogen.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Hydrotreated light distillate (petroleum)	64742-47-8	n.a.	n.a.	A4	n.a.

12. Ecological Information

General Ecological Information

No data available.

Results of PBT and vPvB assessment

CAS# 64742-47-8:

LC50, Bluegill (*Lepomis macrochirus*), 5900. UG/L, 4 D, Mortality, Water temperature: 18.00 C C, pH: 7.50.

Result:

Age Effects.

- Report to Nalco Chemical Company: Four-Day Static Fish Toxicity Studies with D-2303 in Rainbow Trout and Bluegills: IBT No. A615, Hamlin, J., 1971

LC50, Rainbow Trout (*Oncorhynchus mykiss*), 3200. UG/L, 24 H, Mortality, Water temperature: 55.00 C C.

Result:

Abnormal development.

- Nalco D-2303: Toxicity to Rainbow Trout (*Salmo gairdneri*): Test No. 423, McCann, J.A., 1971

